

Technical specifications

General device data		
Hei-PLATE model	Mix 20 l	Mix'n'Heat Core
Dimensions (W × H × D)		168 × 101 × 299 mm
Usable surface heating plate	Ø 145 mm	Ø 135 mm Ø 145 mm
Weight		approx. 3 kg
Maximum permissible load		25 kg
Drive		EC motor, left-turning
Speed range		100 – 1,400 rpm
Protection class (EN 60529)		IP42
Acoustic pressure		< 50 db(A)
Heating		
Heating power	n.a.	800 W at 230 V (EU) 600 W at 115 V (US)
Heating temperature range	n.a.	20 – 300 °C
Heating control	n.a.	PID
Electrical data		
Rated voltage		230 V, 50/60 Hz (EU) 115 V, 50/60 Hz (US)
Connection		L+N+PE
Protection class		I
Oversupply category		II
Degree of pollution		2
Power input		Normal operation 230 V: 825 W (EU) Normal operation 115 V: 625 W (US) Standby mode: 1.7 W
EMC class		B, Group 1
Permissible ambient conditions		
Operating temperature		5 °C – 31 °C at up to 80 % rel. humidity 32 °C – 40 °C at up to 50 % rel. humidity (decreasing linearly)
Installation altitude		up to 2,000 m asl