

IKA

designed for scientists



HB eco

/// Data Sheet

Compact and ergonomic heating bath

- 4 l bath volume
- Max. media temperature: 99 °C
- Ergonomic handles
- Temperature display
- Alternating display of set-point/ actual temperature
- USB interface

www.ika.com

Subject to technical changes



Technical Data

Heat output [W]	1400
Heating temperature range [°C]	room temp. - 99
Heat control	Turning knob
Set temperature resolution [K]	±1
Controller oscillation (3 l water / 90 °C) [K]	±1
Absolute deviation/mean (3l water / 90 °C) [K]	±2
Speed display	LED
Filling volume max. [l]	4
Filling point min. [mm]	60
Material in contact with medium	stainless steel 1.4404
Fixed safety circuit [°C]	109
Class designation acc. DIN 12876	I
Outer diameter [mm]	257
Inner diameter [mm]	225
Outer height [mm]	190
Inner height [mm]	130
Dimensions (W x H x D) [mm]	330 x 190 x 325
Weight [kg]	3.9
Permissible ambient temperature [°C]	5 - 40
Permissible relative humidity [%]	80
Protection class according to DIN EN 60529	IP 21
USB interface	yes
Voltage [V]	100 - 120
Frequency [Hz]	50/60
Power input [W]	1450
Power input standby [W]	3